

TITLE OF INVENTION

"ROTATING FILM SHELL AND TUBE TYPE HEAT EXCHANGER - EVAPORATOR"

FIELD OF INVENTION

The present invention relates to an indirect transfer of heat in shell and tube type heat exchangers and evaporators between the fluids passing through the heat exchange tubes and the shell. More specifically, the invention relates to a shell and tube type heat exchangers and evaporators in which the fluid passing through the heat exchange tubes is a two-phase fluid of a boiling liquid and vapour as encountered in applications involving vapour-liquid separation and in evaporation of refrigerants.

BACKGROUND.

Briefly, the shell and tube heat exchangers and evaporators are devices comprising a plurality of heat exchange tubes encased within a single larger shell involving an indirect transfer of heat between a fluid passing through the tubes and another fluid passing through the shell. The fluid passing through the tubes may be a liquid or a two-phase fluid of a boiling liquid and vapour and the fluid passing through the shell may be a liquid, condensing vapour or a gaseous fluid.

The information on the involved heat transfer mechanism and on the design of the various types shell and tube heat exchangers and evaporators is presented in "Chemical Engineer's Handbook, Fifth Edition, R.H. Perry and C.H. Chilton, McGraw-Hill Book Company, New York, Sections 10 and 11", in "Equipment Design Handbook for Refineries and Chemical Plants, Volume 2, Frank L. Evans, Jr., by Gulf Publishing Company, Houston, Texas, 1974", and in "Compact Heat Exchangers, Second Edition, W.M. Kays and A.L. London, McGraw-Hill Book Company".

In refrigeration, the shell and tube evaporator is a component of a vapour compression refrigeration system that includes a refrigerant circulating in a closed loop between the evaporator, compressor, condenser and an expansion valve. It is used for evaporation of the refrigerant. The principles of refrigeration are presented in the Chemical Engineer's Handbook, Fifth Edition, R.H. Perry and C.H. Chilton, McGraw-Hill Book Company, New York, Sections 12.

The physical, chemical, thermodynamic and transport properties of the various substances and refrigerants that

can be circulated through the heat exchange tubes, or that can be used as the second fluid, are presented in "Chemical Engineer's Handbook, Fifth Edition, R.H. Perry and C.H. Chilton, McGraw-Hill Book Company, New York, Section 3", and in "Handbook of Chemistry and Physics, Forty Ninth Edition, R.C. Weast, Ph.D., Published by The Chemical Rubber Co., Cleveland, Ohio, 1968".

The information on a two-phase flow in channels and on separation of droplets by gravity and centrifugal acceleration is presented in "Chemical Engineer's Handbook, Fifth Edition, R.H. Perry and C.H. Chilton, McGraw-Hill Book Company, New York, Sections 5 and 19".

10 The current art shell and tube evaporators used in vapour compression refrigeration systems suffer from an uneven distribution of the liquid refrigerant into the plurality of the heat exchange tubes and from stratification of the refrigerant vapour - liquid mixture inside the heat exchange tubes causing only a fraction of the internal wall of the heat exchange tube being utilized for boiling, resulting in low overall heat transfer rates of 200 - 400 BTU/ft²/hr/°F. More, the current art evaporators suffer from considerable entrainment of the liquid refrigerant causing impairment of the overall efficiency of the refrigeration system.

To improve the performance and efficiency of evaporators used in refrigeration systems, an improved distributor for the refrigerant vapour liquid mixture is described in U.S. Pat. No. 5,842,351 and various different forms of heat exchanger tubes and inserts in U.S. Pat. Nos. 2,318,206, 3,244,601, 3,339,631, 4,034,964, 4,086,959, 4,090,559, 4,183,682, 4,373,578, 4,534,409, 4,658,892, 5,010,643, 5,167,275, 5,454,429 and 6,092,589. However, none of these previously known devices include the structural and operational features of the instant invention, nor are they as readily constructed at low cost.

SUMMARY OF THE INVENTION

30 The present invention includes a shell and tube type heat exchanger - evaporator that has a plurality of heat exchange tubes provided with an internal baffle that converts the straight tube channel of a standard heat exchange tube into two semi - circularly sectioned spiral channels. The two spiral channels define a spiralling flow path for the vapour generated in the heat exchange tube from a boiling liquid. The generated vapour flows through the two spiral channels with increasing velocity driving the unevaporated boiling liquid in a spirally rotating film of diminishing thickness over the whole internal wall of the heat exchange tube increasing the overall heat transfer rate and the heat exchange capacity of the heat exchange tube. The evaporator's intake nozzle distributes a vapour-liquid mixture into the plurality of the heat exchange tubes via a full cone spray. The fine droplets of boiling liquid entering the heat transfer tubes and those generated during the boiling process are

continuously separated from the generated vapour by impingement on the body of the internal baffle and by centrifugal acceleration of the spiralling flow of the generated vapour. Because of the rotation of the generated vapour and boiling liquid in the heat exchange tube, the heat exchanger-evaporator of the invention can operate with high efficiency in a horizontal position or in vertical position either as a down flow or an up flow unit.

The main object of this invention is to increase the overall heat transfer rate of the current art shell and tube type heat exchangers - evaporators by providing a rotating film of boiling liquid of diminishing thickness on the internal walls of the heat exchange tubes.

10 Another object of this invention is to eliminate the entrainment of the current art shell and tube type evaporators by separating the fine droplets of the boiling liquid from the generated vapour by a combined mechanism of impingement and centrifugal acceleration.

Another object of the invention is to provide for the heat exchange tube of the current art shell and tube type heat exchangers and evaporators a baffle that would change the current straight flow path of a mixture of boiling liquid and vapour to a rotating flow path of separated boiling liquid and vapour.

Another object of the invention is to provide for a heat exchange tube of shell and tube type heat exchangers and evaporators a baffle that would minimally restrict the cross sectional area of the heat exchange tube.

20 Another object of the invention is to provide for a heat exchange tube of a shell and tube type heat exchangers and evaporators a baffle that could be readily inserted into and held in the heat exchange tube.

Another object of the invention is to provide for a heat exchange tube of a shell and tube type heat exchangers and evaporators a baffle that could be manufactured from a suitable plastic or metal material.

Another object of the invention is to provide a shell and tube type heat exchanger-evaporator that could operate in horizontal position or in vertical position as a down flow or an up flow unit with high efficiency.

30 Another object of the invention is to provide for a shell and tube type evaporator an intake nozzle that would evenly distribute the recirculating boiling liquid into the plurality of the heat exchange tubes.

A final object of this invention to be specifically enumerated in here is to provide for a heat exchange tube of a shell and tube type heat exchanger - evaporators an internal baffle and a distributor which will be of simple

construction, easy to use, economically feasible, long lasting and would provide trouble-free operation.

These together with other objects and advantages of the invention will become apparent from an examination of the following description and the appended drawings and claims.

BRIEF DESCRIPTION OF DRAWINGS.

Fig. 1 is a schematic illustration of a sectional view of a preferred embodiment of a rotating film horizontal shell and tube type heat exchanger - evaporator of the invention.

10 Fig. 2 is a longitudinal cutaway view of one heat exchange tube assembly of the invention.

Fig. 3 represents an enlarged view of a transverse section taken along the line A-A of the heat exchange tube assembly of Fig. 2.

Fig. 4 is a view of a preferred embodiment of the internal baffle of the invention used in the heat exchange tube assembly of Fig. 2.

Fig. 5 represents an enlarged view of a transverse section taken along the line A-A of the internal baffle of the invention of Fig. 4.

20

Fig. 6 represents an enlarged view of a transverse section showing a cross sectional profile of an internal baffle of another preferred embodiment of the invention.

Fig. 7 is a schematic illustration of a sectional view of a preferred embodiment of a vertical down flow shell and tube type heat exchanger - evaporator of the invention illustrated in Fig. 1.

Fig. 8 is a schematic illustration of a sectional view of a preferred embodiment of a vertical up flow shell and tube type heat exchanger - evaporator of the invention illustrated in Fig. 1.

30 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS.

While the present invention may be used with the various types shell and tube heat exchangers and evaporators described in the cited references, it has particular application in evaporators used in the vapour

compression refrigeration systems for evaporation of a refrigerant.

In a typical vapour compression refrigeration system, not shown in here, the refrigerant is being circulated by a compressor in a closed loop between an evaporator, compressor, condenser and an expansion valve. The expansion valve changes the high pressure liquid refrigerant to a low pressure - low temperature refrigerant vapour - liquid mixture, the composition and temperature of which is fixed by the pressure and temperature of the liquid refrigerant entering the expansion valve and the operating pressure of the evaporator. The evaporator is being used to indirectly cool a second fluid by boiling and evaporating the refrigerant. The second fluid may be water, brine, glycol, oil, an industrial gas, air or vapour.

10 One preferred embodiment of a shell and tube type heat exchanger -evaporator of the invention intended for cooling of a second fluid (liquid) by boiling and evaporating first fluid (refrigerant) is schematically illustrated in Fig. 1.

20 The heat exchanger - evaporator 1 includes shell 2 provided at first end with fixed tube sheet 3 and at the second end with fixed tube sheet 4. Shell 2 is also provided with an intake nozzle 5 and exit nozzle 6. At its first end the evaporator has a stationary head flange 7 attached to head bonnet 8 provided with refrigerant intake nozzle 9 and, at its second end it has a stationary head flange 10 attached to head bonnet 11 provided with refrigerant exit nozzle 12. The shell space is separated by baffles 13, held in position by tie rods and spacers 14, into a number of compartments directing the flow of a second fluid 15 through the shell space as indicated by arrows 16.

The heat exchanger - evaporator 1 is provided with a plurality of heat exchange tubes 17 provided with internal baffles 20 extending between the stationary tube sheets 3 and 4, with the heat exchange tubes 17 being in direct fluid communication with chambers of said head bonnets 8 and 11.

30 Intake nozzle 9 positioned in the centre of the head bonnet 8 sprays the refrigerant vapour - liquid mixture 18 into plurality of heat exchange tubes 17 via a full cone spray indicated by the broken lines 19. Nozzle 9 which produces a full cone spray of an angle of about 120° is commercially available in a number of different sizes and of cone angles and therefore, it is not further described in here. The refrigerant vapour-liquid mixture 18 is forced through the plurality of heat transfer tubes 17 by the refrigerant compressor (not shown in here). The heat for boiling of refrigerant is provided by the second fluid 15 and is transferred to the refrigerant indirectly through the heat exchange tubes 17 from the second fluid 15 passing through the shell space.

As illustrated in Fig. 2 and Fig. 3 in more detail, a tube assembly of one preferred embodiment of the invention comprises a standard heat exchange tube 17 provided with an internal baffle 20. The internal baffle 20 converts the straight tube channel into two semi - circularly sectioned spiral channels 21a, 21b. The two spiral channels define a spiralling flow path 22 for the refrigerant vapour 23 generated in the heat exchange tube from a film of liquid refrigerant 24 entering the tube 17 with the refrigerant vapour-liquid mixture 18. The generated refrigerant vapour, indicated by arrows 23, flows through the two spiral channels 21a, 21b with increasing velocity driving the unevaporated refrigerant film 24 through the tube 17 in a spirally rotating film of diminishing thickness as indicated by arrows 25, increasing the heat transfer rate on the inside of the heat exchange tube 17. The heat exchange tube 17 is provided with removable ring 26 positioned at the exit end of the heat exchange tube 17 to lock the internal baffle 20 within the heat exchange tube 17. The outside diameter of the heat exchange tubes, depending on application, may vary from 3/8" to 2.5", with a preferred diameter of tubes used in refrigeration systems ranging from 0.5" - 0.75".

The refrigerant vapour-liquid mixture 18, depending on the properties of the used refrigerant, enters the heat exchange tubes 17 at a preferred superficial velocity ranging from 2 to 7 ft/sec and the vaporised refrigerant 23 exits the heat exchange tubes at superficial velocities ranging from 10 to 35 ft/sec.

The diameter of droplets, generated by the refrigerant intake nozzle 9 entering the heat transfer tube 17, varies in the range from 100 to 2000 microns, with their terminal (gravity) settling velocities, depending on the properties of the refrigerant, increasing with a droplet diameter from about 1 ft/sec for a 100-micron diameter droplet to about 7 ft/sec for a 2,000 micron diameter droplet. The size of droplets generated in the boiling process varies in the range from 5 microns to 200 microns, with the terminal (gravity) settling velocity of the 5-micron diameter droplet of about 0.008 ft/sec.

As the volumetric ratio of the refrigerant vapour and liquid at the entrance of the heat transfer tubes 17, depending on the refrigerant properties, varies in the range from 10 to 50 and is increasing to infinity with evaporation of the liquid refrigerant, the refrigerant vapour drives the refrigerant liquid on the inside walls of the heat exchange tubes in a rotating film of increasing radial velocity. As a result, the liquid refrigerant is being boiled and evaporated at a high rate that is limited and controlled by the heat transfer rate occurring on the outside wall of the heat transfer tube.

As the liquid refrigerant boils and evaporates as it passes through the two spiral channels in the heat exchange tube, the droplets of refrigerant entering the heat exchange tube with the refrigerant vapour-liquid mixture 18 and those generated in the boiling process are separated from the refrigerant vapour 23 by impingement on the

body of the internal baffle 20 and by the centrifugal acceleration of the spiralling flow of the vaporized refrigerant 23 of increasing radial velocity. As an example, the centrifugal acceleration for typical refrigerants at the entrance of the heat exchange tube is in a range from 10g to 50g and increases along the tube up to about 200g to 1,000g at the tube exit. Thus, due to the high centrifugal acceleration of the refrigerant vapour at the exit end of the heat exchange tube, there is no entrainment of fine droplets of refrigerant out of the heat exchange tube assembly of this invention.

As illustrated in Fig. 4 and Fig. 5, the internal baffle 20 has a length "L", pitch "p" and a cross sectional profile defined by the thickness "t", radius "r", and diameter D, all being provided to induce the desired rotation of the vaporized refrigerant and of the refrigerant liquid film on the internal wall of the heat exchange tube 17 to increase the heat exchanging capacity of the heat exchange tube 17 and to separate the fine droplets of refrigerant from the refrigerant vapour 23. The preferable length "L" of the tube and baffle 20 is in the range from 6 to 15 feet, the baffle pitch "p" in the range from 1 to 5 inches and the baffle radius "r" in the range from 0.1 D to 0.5 D, where D is the internal diameter of the heat exchange tube 17.

The internal baffle 20 is made of a material that is chemically compatible with the metal heat exchange tube 17, operating temperature and the refrigerant flowing through the heat exchange tube 17 and that does not otherwise impose practical or application problems. As an example, depending on the preferred manufacturing process, the baffle 20 may be made of polyethylene, polypropylene, Teflon, aluminum, high-alloyed austenitic steel, nickel-chromium alloys or Monel. Of these, the least expensive and preferred materials are the polyethylene and polypropylene, that provide easy manufacturing and optimum strength and flexibility required for easy insertion of the baffle 20 into the heat exchange tube 17.

The centrifugal acceleration induced by the internal baffle 20 depends on the properties of refrigerant, baffle dimensions "p", "t", "r", "D" and superficial velocity of the vaporised refrigerant 23 in the heat exchange tube 17. The preferred centrifugal acceleration at the heat exchange tube entrance is in a range from 10g to 50g and at the tube exit in a range from 200g to 1,000g and may be varied by the baffle pitch "p".

While the embodiment of the invention described in Figs. 2, 3, 4 and 5 shows the baffle 20 having a constant pitch "p" along the baffle length "L", it can be appreciated by those with skill in the art that for applications with different refrigerants and different compositions of the refrigerant vapour - liquid mixture 18 entering the evaporator 1, it may be preferable to have a varied or a different pitch "p" at the entrance, along the central portion of the tube length "L" or at the end part of the tube.

While the embodiment of the invention described in Figs. 2, 3, 4 and 5 shows the baffle 20 having a cross sectional profile defined by dimensions "t", "r", "D" with a constant thickness "t", it can be also appreciated by those with skill in the art that baffle 20 may have a different cross sectional profile, while still providing the desired rotating spiralling flow of the refrigerant vapour and liquid film described in Figs. 2 and 3. As an example, Fig. 6 shows a cross sectional profile of the internal baffle of another embodiment of the invention that would also provide the rotating spiralling flow of the refrigerant vapour and liquid film described in Figs. 2 and 3.

While the embodiment of the invention described in Figs. 1, 2 and 3 shows the heat exchange tubes 17 as straight tubes with smooth internal and external wall surfaces, it can be also appreciated by those with skill in the art that the heat exchange tubes 17 may be of various metal compositions, with smooth or with sintered metal deposit coated internal wall surfaces and with smooth or extended outside wall surfaces provided by the various commercially available axial or radial fins, that the tubes may be also of a U-type shape and that they may or may not be provided with the end ring 26.

While the embodiment of the invention described in Figs. 1, 2, 3, 4 and 5 shows a specific configuration of a shell and tube type heat exchanger 1, it can be also appreciated by those with skill in the art that the invention illustrated in Fig. 2, 3, 4 and 5 can be also effectively used in the various types shell and tube type heat exchangers and evaporators described in detail in the cited references and, with the body of the shell 2 being of a circular or a rectangular shape with or without the baffles 13.

While the embodiment of the invention illustrated in Figs. 1, 2, 3, 4 and 5 was described in an application with the first fluid being a refrigerant and the second fluid a liquid, it can be also appreciated by those with skill in the art that the invention can be also used in other heat exchange applications involving a single or two phase fluids with properties described in the cited references.

Fig. 7 is a schematic illustration of a sectional view of another preferred embodiment of the invention showing a vertical down flow rotating film shell and tube type evaporator 1 having the heat exchange tubes 17 provided with internal baffles 20 of the invention described in Figs. 2, 3, 4 and 5.

Fig. 8 is a schematic illustration of a sectional view of another preferred embodiment of the invention showing a vertical up flow rotating film shell and tube type evaporator 1 of the invention having the heat exchange tubes 17 provided with internal baffles 20 of the invention described in Figs. 2, 3, 4 and 5.

While the present invention has been described with reference to specific embodiments in a specific application

to demonstrate the features and advantages of the invention, such specific embodiments are susceptible to modifications to fit other configurations or other applications. Accordingly, the forgoing description is not to be construed in a limiting sense.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000